

<u>1876 The Professional Range All Purpose Wallpaper Adhesive</u> <u>Technical Data Sheet</u>

Description

1876 The Professional Range All Purpose Wallpaper Adhesive is a traditional, high quality, easy to mix flake adhesive. It is easily spread with excellent slip properties for accurate positioning and long-lasting results. Suitable for hanging all wallpaper types.

Directions

<u>Preparation</u>: Ensure surface is clean, dry and free from dust. Treat areas where there is a high risk of mould growth with Bartoline Fungicidal Wash. Size absorbent surfaces before use and allow to dry completely before papering.

<u>Mixing</u>: Add the correct volume of cold water to a clean bucket based on the mix ratio table. Sprinkle the contents of the sachet into the water and stir briskly for 30 seconds to evenly mix. Leave to stand for 3 minutes then stir again thoroughly. The paste is now ready to use.

<u>Pasting:</u> Follow the wallpaper manufacturer's instructions. Soak heavy and embossed paper until supple. Paste generously, particularly the edges, and do not overspread. Take care to avoid getting adhesive on the patterned side of the paper, removing any splashes with a damp sponge. When applying paste the wall wallpapers apply paste directly onto the surface to be papered.

Mix Ratio Tables

<u>5 Roll</u>

APPLICATION	Quantity of cold water to use per sachet	Approximate coverage per sachet*	
Normal wallpapers including woodchip	6 Pints / 3.4 Litres	4 - 5 Rolls	
Vinyl wallcoverings, washables and Novamura	5 Pints / 2.8 Litres	4 Rolls	
Blown vinyl wallcoverings	5 Pints / 2.8 Litres	4 Rolls	
Embossed papers (e.g. Anaglypta)	4 Pints / 2.3 Litres	2 - 2.5 Rolls	
Heavy embossed papers (e.g. Supaglypta)	3.5 Pints / 2.0 Litres	1.75 - 2 Rolls	
Paste the walls	4 Pints / 2.3 Litres	1.5 - 3 Rolls	
Polystyrene tiles	4 Pints / 2.3 Litres	80 sq ft / 24 m²	

*NB: These figures are intended as a guide only.

SIZING: When sizing walls before papering, mix contents of sachet into 8 pints (4.5 Litres) of cold water.

APPLICATION	Quantity of cold water to use per sachet	Approximate coverage per sachet*		
Normal wallpapers including woodchip	12 Pints / 7 Litres	8 - 10 Rolls		
Vinyl wallcoverings, washables and Novamura	10 Pints / 5.7 Litres	8 Rolls		
Blown vinyl wallcoverings	10 Pints / 5.7 Litres	8 Rolls		
Embossed papers (e.g. Anaglypta)	8 Pints / 4.5 Litres	4 - 5 Rolls		
Heavy embossed papers (e.g. Supaglypta)	7 Pints / 4 Litres	3 - 4 Rolls		
Paste the walls	8 Pints / 4.5 Litres	2 - 4 Rolls		
Polystyrene tiles	8 Pints / 4.5 Litres	48 m²		

*NB: These figures are intended as a guide only.

SIZING: When sizing walls before papering, mix contents of sachet into 16 pints (9 Litres) of cold water.

<u>30 Roll</u>

As per 10 Roll as each box contains 3 X 10 Roll sachets.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Fine Scalings	Visual
Colour	Off White	Visual
Odour	Wallpaper paste	
Flash point	Not Applicable	
VOC content	None	

Packing Specification

<u>Pack</u> <u>Size</u>	<u>Product</u> <u>Code</u>	Pack Barcode	Carton Barcode	<u>Packs</u> <u>Per</u> <u>Carton</u>	<u>Cartons</u> <u>Per</u> <u>Pallet</u>	<u>Packs</u> <u>Per</u> <u>Pallet</u>	<u>Ti</u>	<u>Hi</u>
5 Roll	59942820	5010789942823	05010789840945	40	54	2160	9	6
10 Roll	59942830	5010789942830	05010789785475	25	54	1350	9	6
30 Roll Box (3 X sachets)	59942840	5010789942847	05010789775445	10	30	300	6	5

Customs Tariff Code

3505 1050

Bartoline Limited, Barmston Close, Beverley HU17 0LW, England. Tel: 01482 678710 | Fax: 01482 872606 | E-mail: info@bartoline.co.uk

Shipping Classification

Non-Hazardous for shipping purposes