

SAFETY DATA SHEET

Professional Water-Based Floor Sealer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Professional Water-Based Floor Sealer

Product description : Coating.

Product type : Liquid.

UFI : AUWA-AJC3-6NJS-W2V7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Consumer use Industrial use Professional use		

Uses advised against	Reason	
None identified.	-	

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium

Telephone no.: +32 (0) 13 460 200

Fax no.: +32 (0) 13 460 201

Tor Coatings Limited

Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom

Telephone no.: +44 (0) 191 4106611 Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

<u>Supplier</u>

Telephone number : +44 870 8200418 / +44 2038073798

Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 1/15

Professional Water-Based Floor Sealer

SECTION 2: Hazards identification

Precautionary statements

General : P103 - Read carefully and follow all instructions.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention: Not applicable.Response: Not applicable.Storage: Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Supplemental label elements : Detergents - Regulation (EC) No

907/2006

: Not applicable.

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	≤0,1	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2,	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 EC: 611-341-5 CAS: 55965-84-9 Index: 613-167-00-5	≤0,1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1]

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 2/15

Professional Water-Based Fl	oor Sealer			
SECTION 3: Composition/information on ingredients				
		Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)		
		See Section 16 for the full text of the H statements declared		

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

SCL (Specific Concentration Limits) 1,2-benzisothiazol-3(2H)-one	H317 = 0.05 %
	H317 = 0.0015 %
ATE (acute toxicity estimates) Not applicable.	Not applicable.
	Particle Size Not applicable.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Protection of first-aiders

4.1 Description of first a	id measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version: 2 3/15

: No action shall be taken involving any personal risk or without suitable training.

Professional Water-Based Floor Sealer

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire. In case of fire, use DRY

chemicals, CO2, alcohol resistant foam or water spray.

Unsuitable extinguishing

media

: water jet

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

: No unusual hazard if involved in a fire. Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version 4/15

Professional Water-Based Floor Sealer

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures
Advice on general
occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 5/15

Professional Water-Based Floor Sealer

SECTION 8: Exposure controls/personal protection

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Recommended: safety glasses with side-shields (EN 166)

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

For prolonged or repeated handling, use the following type of gloves: nitrile rubber (EN 374) (breakthrough time) >8hours

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140).

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 6/15

Professional Water-Based Floor Sealer

SECTION 8: Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state : Liquid. Colour Colourless. : Not available. Odour : Not available. **Odour threshold**

Melting point/freezing point

Initial boiling point and

boiling range

: >100°C (>212°F) [Literature]

Flammability (solid, gas) Non-flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge, heat and shocks and mechanical impacts.

Nonflammable, but will burn on prolonged exposure to flame or high

temperature.

Upper/lower flammability or

explosive limits

: Not available.

Flash point : Not relevant due to nature of the product. **Auto-ignition temperature** Not relevant due to nature of the product.

: 0°C

Decomposition temperature

Not available.

pH : 8

pH: Justification : Not available. **Viscosity** : Dynamic: 50 mPa·s

Soluble in the following materials: cold water and hot water. Solubility(ies)

Very slightly soluble in the following materials: methanol and acetone.

Solubility in water Not available.

Miscible with water : Yes.

Partition coefficient: n-octanol/: Not applicable.

water

: 2,3 kPa (17,25 mm Hg) [calculated.] Vapour pressure

Evaporation rate : <1 (butyl acetate = 1) **Relative density** : 1,01 to 1,02 [calculated.]

: 1,016758 g/cm³ [20°C (68°F)] [calculated.] Density

Vapour density >1 [Air = 1] **Explosive properties** : Not applicable. **Oxidising properties** : Not available.

Particle characteristics

Median particle size : Not applicable.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version 7/15

Professional Water-Based Floor Sealer

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,171 mg/l	4 hours
,	LD50 Dermal LD50 Oral	Rabbit Rat	92,4 mg/kg 64 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	490	N/A	N/A	0,5	N/A
	64	92,4	N/A	N/A	0,171

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 Percent	-
,	Skin - Severe irritant Eyes - Severe irritant	Rabbit Rabbit	-	-	1 to 4 hours

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 8/15

Professional Water-Based Floor Sealer

SECTION 11: Toxicological information

Conclusion/Summary

Skin
 Based on available data, the classification criteria are not met.
 Eyes
 Based on available data, the classification criteria are not met.
 Respiratory
 Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	skin	Guinea pig Guinea pig	Sensitising Sensitising

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes

of exposure

: Routes of entry anticipated: Oral, Inhalation. Routes of entry not anticipated: Dermal.

Potential acute health effects

Eye contact : Slightly hazardous by the following route of exposure: of eye contact (non-irritant)

Inhalation : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Ingestion: No known significant effects or critical hazards. However, in compliance with good

industrial hygiene practice, exposure to any chemical should be kept to a minimum.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 9/15

Professional Water-Based Floor Sealer

SECTION 11: Toxicological information

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : N

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Endocrine disrupting

properties

: Not available.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,11 mg/l	Algae	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish	28 days
	Chronic NOEL 0,0403 mg/l	Algae	72 hours
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Acute EC50 0,037 mg/l Fresh water	Algae	48 hours
	Acute EC50 0,16 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 0,19 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0,004 mg/l Marine water	Algae	48 hours
	Chronic NOEC 0,18 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,02 mg/l Fresh water	Fish	38 days

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 10/15

Professional Water-Based Floor Sealer

SECTION 12: Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-	OECD 303A OECD 301D	>90 % - Readily - 1 days >60 % - Readily - 28 days	-	-
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7]	0202 00.2	20 70 11000011, 20 000,0		
and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:				
1)	-	<50 % - 10 days	-	_

Conclusion/Summary

: This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	-	-	Readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	-0.83 to 0.75	-	low low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

coemoient (100)

Mobility : Non-volatile.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting

properties

: No known significant effects or critical hazards.

12.7 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 11/15

Professional Water-Based Floor Sealer

SECTION 13: Disposal considerations

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version: 2 12/15

Professional Water-Based Floor Sealer

SECTION 15: Regulatory information

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Annex XVII - Restrictions : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: IIA/i. One-pack performance coatings. EU limit value for this product : 140g/l (2010.)

This product contains a maximum of 140 g/l VOC.

Industrial emissions (integrated pollution prevention and control) -

. Air

: Not listed

: Not listed

Industrial emissions (integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EC)

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

United Kingdom: Great Britain

References : EH40/2005 Workplace exposure limits

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2020/878

REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council

Directive 89/686/EEC

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

CN code : 3209 10 00 00

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 13/15

Professional Water-Based Floor Sealer

SECTION 15: Regulatory information

Europe : All components are listed or exempted.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : Not determined.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

United Kingdom: Great Britain

Full text of abbreviated H statements

_		
:	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H310	Fatal in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H330	Fatal if inhaled.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.

Date of issue/Date of revision : 30/07/2021 Date of previous issue : 30/07/2021 Version : 2 14/15

Professional Water-Based Floor Sealer

SECTION 16: Other information

Full text of classifications [CLP/GHS]

Acute Tox. 2 **ACUTE TOXICITY - Category 2** Acute Tox. 3 **ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4** Acute Tox. 4

Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic

Chronic 1

Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Chronic 2

Eve Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2

Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A

Date of printing Date of issue/ Date of : 30/07/2021 : 30/07/2021

revision

Date of previous issue : 30/07/2021 : 2

Version

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.