



SAFETY DATA SHEET

Wood Dye

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Wood Dye
Product description : Coating.
Product type : Liquid.
UFI : MHTA-KJEM-8NJF-3S4Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	
Uses advised against	Reason
None identified.	-

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE
Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium
Telephone no.: +32 (0) 13 460 200
Fax no.: +32 (0) 13 460 201

Tor Coatings Limited
Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom
Telephone no.: +44 (0) 191 4106611
Fax no.: +44 (0) 191 4920125
enquiries@tor-coatings.com

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

1.4 Emergency telephone number

[National advisory body/Poison Centre](#)

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798
Great Britain

Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

[Classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Flam. Liq. 3, H226
STOT SE 3, H336
Asp. Tox. 1, H304

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Wood Dye

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H336 - May cause drowsiness or dizziness.

Precautionary statements

General :

P103 - Read carefully and follow all instructions.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.

Response :

P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage :

P405 - Store locked up.
P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients :

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics

Supplemental label elements :

EUH066 - Repeated exposure may cause skin dryness or cracking.

Supplemental label elements :

Not applicable.

Supplemental label elements : Detergents - Regulation (EC) No 907/2006

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Yes, applicable.

Tactile warning of danger :

Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification :

None known.

Wood Dye

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5	≥75 - ≤90	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066 See Section 16 for the full text of the H statements declared above.	-	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.

Wood Dye

SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

Wood Dye

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Wood Dye

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

United Kingdom: Great Britain

Product/ingredient name	Exposure limit values
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	EH40/2005 WELs (United Kingdom (UK), 8/2007). STEL: 850 mg/m ³ , (as turpentine (150 ppm)) 15 minutes. Form: Vapour TWA: 566 mg/m ³ , (as turpentine (100 ppm)) 8 hours. Form: Vapour

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Wood Dye

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	DNEL	Long term Dermal	208 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	871 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	125 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	185 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population [Consumers]	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
xylene (mixture of isomeres)	Fresh water	0,327 mg/l	Sensitivity Distribution
	Marine water	0,327 mg/l	Sensitivity Distribution
	Fresh water sediment	12,46 mg/kg	Equilibrium Partitioning
	Marine water sediment	12,46 mg/kg	Equilibrium Partitioning
	Soil	2,31 mg/kg	Equilibrium Partitioning
ethylbenzene	Sewage Treatment Plant	6,58 mg/l	-
	Fresh water	0,1 mg/l	-
	Marine water	0,01 mg/l	-
	Fresh water sediment	13,7 mg/kg	-
	Marine water sediment	1,37 mg/kg	-
2-methylpropan-1-ol	Soil	2,68 mg/kg	-
	Sewage Treatment Plant	9,6 mg/l	-
	Fresh water	0,4 mg/l	-
	Marine water	0,04 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	1,52 mg/kg	-
	Marine water sediment	0,125 mg/kg	-
	Soil	0,0699 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Wood Dye

SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A) (EN 140)

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Various
Odour	: Hydrocarbon.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.

Wood Dye

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	162	323,6	ASTM D 1078

- Flammability (solid, gas)** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
- Lower and upper explosion limit** : Lower: 0,6%
Upper: 8%
- Flash point** : Closed cup: 42°C (107,6°F) [Literature]
- Auto-ignition temperature** : Not relevant due to nature of the product.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- pH : Justification** : Product is non-soluble (in water).
- Viscosity** : Dynamic (room temperature): <38 mPa·s [ISO 2431]
Kinematic (40°C): <20,5 mm²/s
- Solubility(ies)** :

Media	Result
cold water	Not soluble
hot water	Not soluble

- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	1,5001	0,2	calculated.			

- Evaporation rate** : Not available.
- Relative density** : Not available.
- Density** : 0,8 to 0,85 g/cm³ [20°C (68°F)] [DIN 53217]
- Vapour density** : >1 [Air = 1]
- Explosive properties** : Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. No unusual hazard if involved in a fire.
- Oxidising properties** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.

Wood Dye

SECTION 10: Stability and reactivity

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	10000	N/A	N/A	N/A	N/A

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	skin	Rabbit	Not sensitizing

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Wood Dye

SECTION 11: Toxicological information

Product/ingredient name	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Based on available data, the classification criteria are not met.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Wood Dye

SECTION 11: Toxicological information

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	Acute NOEC 100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0,23 mg/l	Daphnia spec.	-
	Chronic NOEC 0,131 mg/l	Fish	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	OECD 301B	>80 % - Readily - 28 days	-	-
	OECD 301F	>80 % - Readily - 28 days	-	-

Conclusion/Summary : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	-	100%; < 28 day(s)	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	5 to 6.5	-	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Volatile.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Wood Dye

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	Paint	Paint	Paint	Paint
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	Limited quantity ≤ 5L Tunnel code (D/E)		Emergency schedules F-E ; S-E Remarks : ≤ 5L: Limited Quantity - IMDG 3.4	Quantity limitation Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344.

Wood Dye

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other EU regulations

VOC :
VOC for Ready-for-Use Mixture : IIA/f. Interior and exterior minimal build woodstains. EU limit value for this product : 700g/l (2010.)
This product contains a maximum of 700 g/l VOC.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

United Kingdom: Great Britain

UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Aerosol dispensers :

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

Wood Dye

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

CN code : 3208 10 90 00

Inventory list

Australia	: At least one component is not listed.
Canada	: At least one component is not listed.
China	: At least one component is not listed.
Eurasian Economic Union	: Russian Federation inventory : Not determined.
Japan	: Japan inventory (CSCL) : At least one component is not listed. Japan inventory (ISHL) : At least one component is not listed.
New Zealand	: At least one component is not listed.
Philippines	: At least one component is not listed.
Republic of Korea	: At least one component is not listed.
Taiwan	: At least one component is not listed.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Wood Dye

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304	Expert judgment Expert judgment Expert judgment

Full text of abbreviated H statements

United Kingdom: Great Britain

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 05/07/2022

Date of issue/ Date of revision : 05/07/2022

Date of previous issue : 05/07/2022

Version : 4

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.