



Technical Data Sheet

Blackfriar MDF Primer Undercoat

An excellent quick drying all-in-one primer/undercoat specially formulated for MDF. May also be used as a primer/undercoat over interior masonry, dry plaster and cement.

Performance characteristics –

- Fast drying.
- All-in-one primer and undercoat.
- Good opacity.
- Excellent adhesion to MDF.
- Interior use.

Preparation - Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Exposed ferrous metal (eg. nails) should be spot primed with the appropriate Blackfriar metal primer.

Application - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. Two coats are recommended to give best protection. For porous surfaces or if applying by spray the product may thinned up to 10% with water.

Thinning - Maximum 10% water.

Limitations - Do not use under cold (less than 10°C), damp or humid conditions. Not suitable for use on metal surfaces. Use Blackfriar Metal Primer or Blackfriar Multi-Surface Primer.

Coverage - Up to 14m² per litre per coat.

Drying Time - Touch dry in 1 - 2 hours. Recoat after 4 hours. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

Clean Up - Remove as much product as possible from

application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Storage - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

May produce an allergic reaction.

Safety data sheet available on request.

EU limit values: 50g/l (2007) 30g/l (2010.) This product contains a maximum of 30g/l VOC

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.