



Technical Data Sheet

Blackfriar Professional Paint and Varnish Remover

Blackfriar Paint & Varnish Remover removes old coatings quickly and effectively. It works on a variety of finishes including gloss and emulsion paints, varnish and French polish. Effective on wood, metal and glass, the fast-acting formula has a non-drip consistency, which makes it easy to apply to all surfaces. It will not discolour or raise the grain of wood.

Performance characteristics –

- Fast-acting
- For wood, metal and glass self-neutralising
- Removes and strips multiple coats easily.
- Does not discolour or raise wood grain.
- Non caustic.
- No washing down required in most cases.
- Softens and renews brushes.
- Easy to use.

Preparation - Wear protective clothing, eye protection and gloves. Protect all surfaces not to be stripped from spillage or splashes with a waterproof covering such as polythene sheeting. Store in a cool place and take care when removing the cap as contents can pressurise. Ensure there are no sources of ignition in the proposed application environment. Work outside whenever possible or open all doors and windows to provide good draft and ventilation. Do not use in enclosed spaces.

Application - Read Preparation and Health and Safety Instructions prior to using. We recommend testing on an inconspicuous area first. Apply a generous coat by brush taking care not to overspread. After a few minutes the paint will normally blister and lift. Many paints can then be removed by use of a scraper or wire wool. Thicker build-ups of heavy duty coatings may require extra applications every 30 minutes or until the paint is easily removed back to the original surface. Do not allow the remover to dry out between applications. Remove softened paint with a scraper, use a shave hook, wire wool or an old toothbrush in difficult areas. *After removal, re-coating can begin immediately with oil based paints providing the old coating and all residue*

of stripper has been completely removed, leaving a clean bare surface which is dry and sanded smooth. If re-coating with water-based paints, wash the stripped surface thoroughly with white spirit and leave to dry. Keep this product away from plastic, glassfibre, Perspex® lino, textiles and other vulnerable surfaces.

Clean up - Remove as much product as possible, collecting waste into newspaper and allow to dry off in a safe place, outside. Do not empty into drains or water-courses. Some local authorities have special facilities for the disposal of waste coatings.

Danger

Highly flammable liquid and vapour. Harmful to aquatic life with long lasting effects.

Read label before use. Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

In case of fire: Use water spray, dry chemical powder or carbon dioxide for extinction.

Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.