

PRODUCT DATA SHEET

03/2026

Version 2.0

Product Name	Road/Line Marking Paint	
Our Reference	4980 Line	
Coating Type	Chlorinated rubber/alkyd	
Typical Uses	Fast drying line marking paint for concrete, weathered tarmac, paving, and wood.	
Colours	Yellow 4980-2-7, White 4980-6-3	
Gloss Level	Eggshell (10-15% gloss)	
Theoretical Spreading Rate	Up to 50 linear metres at a line width of 75 microns per litre	
Surface Preparation	Surfaces must be clean and dry.	
Instructions For Use	Stir thoroughly before use. Do not thin the coating as this will reduce opacity. Small areas can be applied by brush.	
Drying Time (20°C)	Touch Dry	10 minutes
	Hard Dry	20 minutes
	Recoat Time	After 20 minutes
Application	Conventional Spray	Thin up to 20% with BT1 thinner.
	Airless Spray	Not Recommended
	Roller	Use as supplied.
	Brush	Use as supplied.
Application Temperature	Substrate temperature must be at least 5°C and no more than 20°C (remember that substrates are often several degrees colder than the air temperature).	
Packaging	5 litres	
Thinner	BT1 (thinning), BT2 (cleaning)	
VOC (Supplied)	500-550 grams/litre depending on colour	
Volume Solids	50%	
Flashpoint	23°C	
Shelf Life/Storage	12 months from date of manufacture in sealed containers. Store in a cool, dry place with temperatures between 5-30 °C and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.	

The information in this data sheet and this product is intended for users who have the requisite knowledge and industrial skills. It is the end-user's responsibility to determine the suitability of the product for its intended use. Bailey Paints has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of this product. Bailey Paints does therefore not accept any liability arising from loss, injury or damage resulting from such use or the contents of this data sheet.