



# 7420 Line Acrylic Floor Paint

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: FLOOR PAINT

**Product code:** 7420 line

**Product description:** Water-based single pack floor paint.

CAS No.:

EC No.:

Index No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Floor paint.

**Uses advised against:** Follow supplier's recommendations on correct use of the

product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: S G Bailey Paints Limited

Unit 15A Griffin Mill London Road

Thrupp Stroud

Gloucestershire

GL5 2AZ

**Telephone:** +44 (0)1453 882237

**E-mail:** richard@baileypaints.co.uk

1.4 Emergency telephone number

**In case of emergency, call:** +44 (0) 7774 460658 (UK number, 24 hours, 7 days)

Version: 1.0 Product code: 7420 line Page 1 of 11

Date: 01/06/24 Product name: W/B Acrylic Floor Paint





### **SECTION 2: Hazard Identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Not classified

#### 2.2 Label elements according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):

None

Signal Word: None

Hazard Statement(s): None
Precautionary Statement(s): None

Supplemental Hazard information

(EU): None

Contains: Not applicable

#### 2.3 Other hazards:

May cause slight skin and eye irritation.

### **SECTION 3: Composition**

#### 3.2 Mixtures

#### Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
2 butoxyethanol  REACH Registration no.: 01-2119475108-36-xxxx	1.5	111-76-2	203-905-0	603-014-00-0	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319

See section 16 for a full description of H statements.

Version: 1.0 Product code: 7420 line Page 2 of 11
Date: 01/06/24 Product name: W/B Acrylic Floor Paint





### **SECTION 4: First Aid Measures**

#### 4.1 **Description of first aid measures**

INHALATION: No first aid action required.

SKIN CONTACT: Remove contaminated clothing immediately. Wash

affected area with soap and water.

**EYE CONTACT:** Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do. Continue rinsing. Seek medical advice if problems

persist.

**INGESTION:** Give small quantities of water to drink. Do NOT induce

vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

May cause slight skin and eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatments needed

If you feel unwell, seek medical advice.

# **SECTION 5: Fire-fighting Measures**

#### 5.1 **Extinguishing Media**

Suitable extinguishing media: Foam, water jet, CO<sub>2</sub> or dry powder.

**Unsuitable extinguishing media:** None

#### 5.2 Special hazards arising from the substance or mixture

This product is not flammable but toxic decomposition products may be formed if it is involved in a fire.

Version: 1.0 Product code: 7420 line Page 3 of 11 Product name: W/B Acrylic Floor Paint

Date: 01/06/24





#### 5.3 Advice for fire-fighters

Prevent run-off from fire control or dilution from entering drains or water courses. Suitable protective clothing and respiratory equipment should be worn in fire conditions. Keep fire-exposed containers cool by spraying with water.

#### **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Avoid contact with skin and eyes. Wear suitable personal protective equipment.

#### 6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (see Section 8). Contaminated clothing should be thoroughly cleaned.

#### 6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

#### 6.3 Methods and materials for containment and clearing up

#### 6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

#### 6.3.2 For cleaning up

Use sand, earth or any suitable adsorbent material to adsorb spillages. Transfer the contaminated absorbent material into sealable containers for disposal. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

#### 6.3.3 Other advice

None

#### 6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

Version: 1.0 Product code: 7420 line Page 4 of 11
Date: 01/06/24 Product name: W/B Acrylic Floor Paint





### **SECTION 7: Handling and Storage**

#### 7.1 Precautions for safe handling

Keep out of the reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. Wear suitable personal protective equipment (see Section 8).

Do not eat, drink or smoke when using this product. Wash exposed skin after use. Contaminated work clothing should not be allowed out of the workplace. Contaminated clothing should be thoroughly cleaned or disposed of.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Keep away from heat and direct sunlight. Store only in the original container. Do not pressurise container. Store in a cool, well-ventilated place. Store upright and protect from frost.

See section 10 for incompatible materials.

#### 7.3 Specific end uses(s)

Floor paint.

# **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1 Control parameters

#### Workplace exposure limits (WEL) - United Kingdom

HSE EH40 for 2-butoxyethanol:

Long-term exposure limit (8-hour TWA reference period): 25ppm/123mgm<sup>-3</sup>

Short-term exposure limit (15-minute reference period): 50ppm/246mgm<sup>-3</sup>

#### Other exposure limits

Consult applicable national legislation for WELs in other countries.

#### **Biological limits**

None assigned.

Version: 1.0 Product code: 7420 line Page 5 of 11

Date: 01/06/24 Product name: W/B Acrylic Floor Paint





**Derived No-Effect Level (DNEL)** 

Not available.

**Predicted No-Effect Concentration (PNEC)** 

Not available.

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation.

**8.2.2 Personal protection:** Appropriate and compliant personal protective

equipment (PPE) must be provided and used.

**Eye protection:** Safety glasses.

**Skin protection:** Appropriate barrier creams.

**Hand protection:** Suitable gloves.

Other: Long sleeve protective clothing.

**Respiratory protection:** Not required.

#### 8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

# **SECTION 9: Physical and Chemical Properties**

#### 9.1 Information on basic physical and chemical properties

Appearance:

Odour:
Characteristic

Odour threshold:
Not available

PH:
Not available

Melting/freezing point:
Not available

Initial boiling point and boiling range:
Not available

Not available

Not flammable

Version: 1.0 Product code: 7420 line Page 6 of 11

Date: 01/06/24 Product name: W/B Acrylic Floor Paint





Evaporation rate:

Flammability (solid; gas):

Upper/lower flammability or explosive limits:

Vapour pressure:

Not available

Not available

Not available

Relative density: 1.205

**Solubility:** Miscible with water

Partition coefficient: n-octanol/water:Not availableAuto-ignition temperature:Not applicableDecomposition temperature:Not available

**Viscosity:** 7.5 – 8.5 poise @ 20°C

Explosive properties: Not explosive Oxidising properties: Not oxidising

9.2 Other information

None

### **SECTION 10: Stability and Reactivity**

**10.1 Reactivity** Not reactive

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** No hazardous reactions expected during normal use.

**10.4 Conditions to avoid**None known

10.5 Incompatible materials None known

**10.6** Hazardous decomposition products If involved in a fire, may liberate toxic smoke and fumes.

# **SECTION 11: Toxicological Information**

#### 11.1 Information on toxicological effects

Acute toxicity Low acute toxicity.

Version: 1.0 Product code: 7420 line Page 7 of 11

Date: 01/06/24 Product name: W/B Acrylic Floor Paint





**Skin corrosion/irritation**May cause slight skin irritation.

**Serious eye damage/irritation** May cause slight eye irritation.

**Skin sensitisation** Not sensitising.

**Respiratory irritation** Not irritating.

**Respiratory sensitisation**No evidence of respiratory sensitisation.

Germ cell mutagenicity Not mutagenic.

**Carcinogenicity** Not carcinogenic.

**Reproductive toxicity**Not classified. The product does not contain substances

classified for reproductive toxicity above the

classification thresholds.

**Specific Target Organ Toxicity – single** 

exposure

No identified effect.

**Specific Target Organ Toxicity –** 

repeated exposure

No identified effect.

**Aspiration hazard** No aspiration hazard.

Information on likely routes of exposure

**Inhalation** No significant effect.

**Skin contact** May cause slight skin irritation.

**Eye contact** May cause slight eye irritation.

**Ingestion** No significant effect.

Symptoms related to the physical, chemical

and toxicological characteristics

May cause slight skin and eye irritation.

Other information None

### **SECTION 12: Ecological Information**

**12.1 Toxicity** The product is low hazard for the environment.

**12.2** Persistence and degradability Not available.

Version: 1.0 Product code: 7420 line Page 8 of 11

Date: 01/06/24 Product name: W/B Acrylic Floor Paint





12.3 Bioaccumulative potential Not expected to bioaccumulate.

12.4 Not available Mobility in soil

12.5 Results of PBT and vPvB assessment Not classified as PBT/vPvB by current EU criteria.

12.6 **Endocrine disrupting properties** No information available.

12.7 Other adverse effects No other adverse effects are expected.

### **SECTION 13: Disposal Considerations**

#### 13.1 Waste treatment methods

Product and packaging to be disposed of as normal industrial waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

# **SECTION 14: Transport Information**

ROAD (ADR) Not classified as hazardous for transport.

14.1 **UN Number** 

14.2 UN Proper shipping name

14.3 Transport hazard class(es)

14.4 Packing group

14.5 **Environmental hazards** 

INLAND WATERWAYS (ADN/ADNR) Not classified as hazardous for transport.

14.1 UN Number

14.2 UN Proper shipping name

14.3 Transport hazard class(es)

14.4 Packing group

**Environmental hazards** 14.5

Version: 1.0 Product code: 7420 line Page 9 of 11 Date: 01/06/24

Product name: W/B Acrylic Floor Paint





**RAIL (RID)**Not classified as hazardous for transport.

14.1 UN Number -

14.2 UN Proper shipping name -

14.3 Transport hazard class(es) -

14.4 Packing group -

14.5 Environmental hazards -

AIR (IATA/ICAO) Not classified as hazardous for transport.

14.1 UN Number -

14.2 UN Proper shipping name -

14.3 Transport hazard class(es) -

14.4 Packing group -

14.5 Environmental hazards -

**SEA (IMDG)**Not classified as hazardous for transport.

14.1 UN Number -

14.2 UN Proper shipping name -

14.3 Transport hazard class(es) -

14.4 Packing group -

14.5 Environmental hazards -

14.6 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

### **SECTION 15: Regulatory Information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP).

15.2 Chemical Safety Assessment

Not applicable.

15.3 VOC content

72 g/l (Category A/i under Directive 2004/42/EC).

Version: 1.0 Product code: 7420 line Page 10 of 11
Date: 01/06/24 Product name: W/B Acrylic Floor Paint





# **SECTION 16: Other Information**

H302: Harmful if swallowed. Full text of relevant H-statements:

H312: Harmful in contact with skin. H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

#### References:

Suppliers' Safety Data Sheets for components Regulation (EC) No. 1272/2008 EH40/2005, 2<sup>nd</sup> Ed., 2011

#### Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

#### Version history:

Version: 1.0

Issue date: 01/06/2024 Previous version: **New SDS** 

Issue date of previous version: Not applicable Sections changed from previous version: Not applicable

Version: 1.0 Product code: 7420 line Page 11 of 11 Date: 01/06/24 Product name: W/B Acrylic Floor Paint