

TECHNICAL DATA SHEET

06/2024

Product Name	7420 line Acrylic Floor Paint	
Description	Protects and transforms both interior and exterior floors with an attractive, tough, durable, and easy to clean coating.	
Performance Characteristics	<ul style="list-style-type: none"> o Indoor and outdoor use o Durable cross-linking acrylic resin o Resistant to grease, oil, and weak acidic and alkali solutions o Suitable for asphalt, tarmac, concrete, brickwork, wood, metal, cement, and stone o ideal for domestic, commercial, and light industrial use 	
Colours	Light grey 00A05 and mid grey 00A09. Ral and British Standard colours mixed to order.	
Gloss Level	Semi-gloss finish	
Surface Preparation	Ensure the surface to be painted is sound, clean, dry, and free from grease or any substance liable to give adhesion problems. Scrape off any old or flaking paint until you have a firm surface. Special attention should be given to areas under cars to ensure all oil, grease, dirt, and road salt is removed. New concrete must be left for at least 6 months before painting. Granolithic and power floated floors will require chemical or mechanical etching.	
Application	<p>Stir thoroughly before use. Normally applied by brush or roller. Can be applied by spray. Bare concrete: the first coat should be thinned 20-30% with water. Previously painted surfaces: apply 1-2 coats as required. Bare wood and metal: paint with a suitable primer before application.</p>	
Theoretical Spreading Rate	8-12m ² per litre. Two coats recommended.	
Drying Time	Touch dry	1 hour @ 20°C
	Hard dry	2 hours @ 20°C
	Recoat	Once touch dry
	Full cure	5-7 days
Clean Up	Remove as much product as possible from equipment then clean with water.	
Storage	Store in cool and dry conditions	