

STABILISING SOLUTION

A solvent based highly penetrating solution designed to stabilise chalking weathered decorative finishes and to control suction on undecorated surfaces. For use on most exterior masonry surfaces and exterior grade building boards.

| AVAILABILITY | |
|--------------------------|--|
| Colour range | Clear |
| Packaging | 5L |
| PROPERTIES | |
| Suitable Surfaces | External render, concrete, masonry, stone, brick, block and most exterior grade building boards |
| Drying time @ 20°C/65%RH | Touch dry: 4 hours Recoat: 16 hours Colder/hotter substrates and temperature conditions will affect drying times |
| Finish | n/a |
| Composition | Pigment: none Resin: Epoxy ester, hydrocarbon Solvent: Dearomatised White Spirit |
| Spreading rate | Up to 6m ² per litre on smooth surfaces. On textured surfaces the spreading rate will be reduced |
| Wet film thickness | n/a |
| Dry film thickness | n/a |
| Volume solids | 26% |
| Flash point | 40°C (closed cup) |
| VOC content | EU limit value for this product (cat.A/h): 750g/l (2010) This product contains max. 749g/l VOC. |
| Limitations | Do not apply if there is a risk of rain, air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or drying period. Do not use on bitumen coatings. The decoration of Fletton brickwork either facings or commons is not recommended. |
| PREPARATION | |
| New Surfaces | All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Fill cracks and small defects in masonry surfaces with Sandtex Ready Mixed Filler and finish to match existing. |



| | |
|---|--|
| | Surfaces with excessive suction should be treated with an application of Sandtex Trade Stabilising Solution . |
| Aged Undecorated or Previously Decorated Surfaces | All surfaces must be sound, suitably dry and free from anything that will interfere with the adhesion of the material to be applied. Remove all loose and failing or suspect material by scraping or brushing with a stiff bristle brush (not wire) to a sound edge. Organic growth must be treated with Sandtex Fungicidal Wash and removed. For surfaces in poor condition mechanical means may be necessary e.g. pressure washing between 1500-2000 psi (102-136 bar), proprietary paint removal system, wet or dry grit blasting. Care must be taken not to damage the underlying surface. Fill cracks and surface defects in masonry surfaces with Sandtex Ready Mixed Filler & finish to match existing. Stabilise all bare, filled and previously decorated chalking areas with an application of Sandtex Trade Stabilising Solution . |
| COATING SYSTEM | Apply in one liberal coat until suction, porous, friable or chalking surfaces are stabilised. Do not over stabilise. |
| APPLICATION | Stir or shake well before use. Apply using good quality tools – synthetic or bristle brush. Do not thin. |
| CLEANING | Return surplus material to container. Clean tools & equipment with a proprietary cleaner immediately after use. |
| STORAGE | Store upright and secure. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not store below 5°C or above 40°C. |
| HEALTH AND SAFETY | Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Customer Relations Team. When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Sandtex Trade products are freely available from the place of purchase or the address below. Do not empty into drains, watercourses or access routes to septic tanks. |
| GENERAL INFORMATION | <p>Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: Code of practice for decorative wallcoverings and painting.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Final results cannot be guaranteed by Crown Paints as it has no control over the conditions under which its products are applied.</p> <p>Before using this product, please ensure you have the latest information. For help or more information contact the Sandtex Trade Customer Relations Team on: Tel: 0330 0240 302. e-mail: info@sandtextrade.co.uk website: www.sandtextrade.co.uk</p> <p>This information is correct at date of issue November 2021.</p> |

