

TECHNICAL DATA SHEET



TIMONOX BONDING PRIMER

A water based adhesion promoting primer which provides an ideal foundation for Crown Trade Timonox flame retardant coating systems. It is suitable for use on both new and old surfaces such as plaster, cement, concrete and previously painted surfaces. It provides good obliteration and permanently blocks out common residual stains such as nicotine, graffiti and smoke stains etc.

AVAILABILITY	
Colour Range	White
Packaging	5L
PROPERTIES	
Suitable Surfaces	Plaster, cement, concrete & previously painted surfaces
Drying Time @ 20°C/65%RH	Under normal drying conditions touch dry in 2 hours and recoat after 16 hours. Allow for adequate ventilation during the drying period
Finish	Matt
Composition	Pigment: Titanium dioxide and extenders
	Binder: Acrylic polymer
	Solvent: Water
Spreading Rate	Up to 12m ² per litre on smooth surfaces
Wet Film Thickness	83 micrometres at 12m ² per litre
Dry Film Thickness	34 micrometres at 12m ² per litre.
Volume Solids	42%
Flash Point	Not applicable
VOC Content	EU limit value for this product (cat.A/g): 30 g/l (2010). This product contains max. 5 g/l VOC.
Limitations	Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period. NOTE: A trial test area is recommended over severely stained or suspect surfaces. For extremely chalky, powdery, charred or unstable surfaces a Crown Trade stabilising solution should be used.
PREPARATION	
New Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. On porous surfaces the first coat of Crown Trade Timonox Bonding Primer can be thinned with up to 10% with clean water
Previously Decorated Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be treated with Sandtex Trade Fungicidal Solution . Fill any fixing holes, cracks and shallow surface defects with Sandtex Ready Mixed Filler . Patch prime bare and filled areas with Crown Trade Timonox Bonding Primer . Wash remaining sound paint or any smoke, graffiti or soiled areas (excluding water stains) with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas are still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Crown Trade Timonox Bonding Primer .



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG. Tel: 01254 704951

Crown Paints Ireland Ltd, Unit 8A, Coolmine Central, Porters Road, Coolmine Ind Est, Dublin 15, D15 AX9A. Tel: 00353 1 8164400

TECHNICAL DATA SHEET



COATING SYSTEM	Apply one coat – see limitations/application.
APPLICATION	<p>Stir well before and during use. Apply using good quality tools – synthetic brush or medium pile roller. For airless spray dilution may be required. For further information follow the spray manufacturer's guidelines.</p> <p>Stains Note: One coat of Crown Trade Timonox Bonding Primer is normally sufficient, however, over severely stained or suspect surfaces a trial test area is recommended before proceeding.</p>
CLEANING	Return surplus material to container. Wash tools & equipment with clean water or a warm soapy solution immediately after use.
STORAGE	Store upright and secure. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not store below 5°C or above 40°C.
HEALTH AND SAFETY	Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Trade Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Do not empty into drains, watercourses or access routes to septic tanks.
GENERAL INFORMATION	<p>Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12: Code of practice for decorative wallcoverings and painting.</p> <p>Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate. Crown Paints is unable to guarantee results as it has no control over the conditions under which its products are applied.</p> <p>Before using this product please ensure you have the latest information. For help or more information contact the Crown Trade Customer Relations Team on: Tel: 0330 0240297 Fax: 0330 0240278 e-mail: info@crowntrade.co.uk website: www.crowntrade.co.uk</p> <p>This information is correct at date of issue November 2021</p>



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG. Tel: 01254 704951

Crown Paints Ireland Ltd, Unit 8A, Coolmine Central, Porters Road, Coolmine Ind Est, Dublin 15, D15 AX9A. Tel: 00353 1 8164400