

CONCRETE & GROUT RESIDUE REMOVER**OVERVIEW**

Concrete & Grout Residue Remover is a liquid formula that will reverse the molecular bonding action of cement back into sand and aggregate, this can be rinsed away with ease leaving the surface undamaged and cement-free.

BENEFITS

- No sulphuric or phosphoric acid - this formula will not damage metals if used correctly.
- No VOCs or ingredients that will harm the environment.
- It can be used to remove: fully cured cement, concrete, mortar, grout or stucco from most surfaces - whilst simultaneously removing rust and oxides
- Will not attack metal surfaces unlike alternative hydrochloric based formulations.
- Safer and easy to use - non flammable formulation that is quick, simple and effective.

IMPORTANT / LIMITATIONS

Keep children and pets away until the treatment is complete and the surface is completely dry.

Do not apply if rain is expected within 4 hours or before the surface is completely dry.

Do not apply to hot surfaces or in direct sunlight.

SURFACE PREPARATION

Surface should be dry and brush away loose deposits before to ensure optimum performance.

Ensure the solution does not spill or splash on any delicate areas

PRODUCT CHARACTERISTICS

Colour	White/Clear
Odour	Mild Detergent
Form	Liquid
PH	2<
Specific Gravity @ 25°C	1.165
Shelf Life	24 months from the date of manufacture in the original unopened container
Application Temperature	Min 5°C : Max 30°C

APPLICATION

This product is ready to use - do not dilute.

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption.

Ensure adequate ventilation at all times and wear protective clothing, gloves and safety goggles.

READ MSDS BEFORE USE

Remove loose deposits from the surface ensuring it is dry and apply concrete dissolver.

Make sure the surface is saturated with product, if the solution evaporates a white residue will appear, do not rinse, simply re-saturate the surface.

Leave for 30 - 60 minutes until the concrete has softened.

Repeat the process until all residues are dissolved. For extremely heavy build up, repeat the cleaning process again or apply 2 coats and leave overnight.

Rinse the surface with cold water high pressure washer.



CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

STORAGE

KEEP OUT OF REACH OF CHILDREN.

24 months from the date of manufacture in original unopened container.

Keep in a dry place.

Do not store below 5°C. Keep out of direct sunlight and protect from frost.

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)