

GK OIL OUT**OVERVIEW**

GK Oil Out is a super concentrated formula and will push oil out from deep within the pores. GK Oil Out removes contamination without leaving a residue. Ideal for stubborn hard to remove grease and oil stains.

Easy to use, GK Oil Out effectively removes stubborn stains and grease from driveways, patios, natural stone (including marble), block paving, wood, decking and all Concrete substrates.

BENEFITS

- Easy to use
- Water rinsable
- Low odour
- Fast and effective
- Non caustic
- Will not damage natural / sensitive surfaces such as marble or granite

APPLICATION

This product is ready to use - do not dilute.

Shake container before use.

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory.

Apply a saturated coat to the affected area using a garden sprayer or applying directly on to the substrate.

Leave the product to work for up to 1 hour depending on the level of staining.

Remove from the surface using hot water or a jet wash.

Repeat the process If staining is still evident until the area is free of contamination.

PRODUCT CHARACTERISTICS

Colour	Colourless
Odour	Barely Perceptible
Form	Liquid
PH	Approximately 7
Shelf Life	24 months from the date of manufacture in the original unopened container
Application Temperature	Min 5°C : Max 30°C

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)