

ULTRA MATT

Ideal for ceilings, **Dulux Trade Ultra Matt** has been formulated to be anti-flashing and provide a dead matt, non-reflective finish at all angles. It has excellent touching-in properties, providing near invisible touch-up for areas in critical lighting

KEY BENEFITS

- Anti-flashing
- Dead Matt Finish, Ideal for Ceilings in Critical Lighting
- Excellent Touching-In Properties

PRODUCT INFORMATION

Typical Use

Suitable for use on all normal interior wall and ceiling surfaces.

Pack Size

3 L & 10L

Colour Range

White only

Composition (nominal)

Pigment: Lightfast pigments

Binder: Copolymer binder

Solvent: Water

Volume Solids

40% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a first coat of **Dulux Trade Drywall Primer Sealer**. The normal finishing process is 2 or 3 full coats of **Dulux Trade Ultra Matt**, however for significant colour change additional coats maybe required.

APPLICATION METHOD

Brush, roller, or airless spray.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Thinning not required.

Spray Recommendations

Airless Spray: For best results use a 515 or 517 Low Pressure tip @ 1300 - 1700 psi (89 – 117 bar).

Alternatively, use a 517 tip @ 2000 – 2400 psi (138 - 165 bar).

Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.



Issued 09/24

549

ULTRA MATT

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 4 hours.

Cleaning Up

After use, remove as much product as possible from brushes before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider

donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 1g/l VOC. VOC content: Trace (0-0.1%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2024.