

## ADVANCED CONTRACT MATT

**Dulux Trade** Advanced Contract Matt is a professional quality matt emulsion with good coverage and opacity, optimised for professional application. Its suitable for interior walls and ceilings, ideal for bare plaster and plasterboard.

### KEY BENEFITS

- Up to 16m<sup>2</sup>/l coverage
- For Walls & Ceilings, Ideal for New Plaster
- Optimised for Professional Application
- Water-based

### PRODUCT INFORMATION

#### Typical Use

Ideal for use on plaster that is still drying out, but also suitable for use on all normal interior wall and ceiling surfaces.

#### Pack Size

10L

#### Colour Range

White only

#### Film Properties

**Chemical Resistance:** Not suitable.

**Heat Resistance:** Not suitable for use on heated surfaces, such as radiators.

**Water Resistance:** Where frequent heavy condensation is likely, as in some kitchens and bathrooms, **Dulux Trade** Diamond Eggshell is more suitable.

**Minimum Recommended Wet Film Thickness:** 55 microns.

#### Composition (nominal)

**Pigment:** Lightfast Pigments.

**Binder:** PVA Copolymer Emulsion.

**Solvent:** Water.

#### Volume Solids

White – 28% (nominal).

### SURFACE PREPARATION

To get the best results with **Dulux Trade** Advanced Contract Matt, make sure surfaces to be painted are sound, clean, dry, and free from all defective or poorly adhering material, dirt, grease, and salts.

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell** Trade **Polyfilla**.

# ADVANCED CONTRACT MATT

## SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade** Advanced Contract Matt (up to 1-part clean water to 5 parts paint). The normal finishing process is 2 full coats of **Dulux Trade** Advanced Contract Matt, however for significant colour change additional coats may be required.

## APPLICATION METHOD

Brush, roller, or Airless spray.

As with other water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

To minimise picture framing or patchy finishes, we strongly recommend stirring the paint thoroughly prior to use. If thinned, the paint used for cutting-in and for rolling should be to the same ratio. Cut in one wall at a time, then rolling immediately afterwards, not allowing the cutting-in to dry prior to rolling. Cut in no more than 5 to 8cm away from any internal angles, including sockets/switches, skirting, architraves, etc. Roll into the cutting-in, ensuring you roll as close to the edge as possible.

### Practical Coverage

A guide to the coverage which can be achieved under normal conditions is up to 16m<sup>2</sup> per litre.

### Thinning

**Sealing new or bare surfaces:** Add up to 1-part clean water to 5 parts paint.

**Normal use (not to be exceeded):** Thinning is not required.

**Airless spray application:** Add up to 1-part clean water to 10 parts paint.

### Spray Recommendations

**Airless Spray:** For best results use a 517 Low Pressure tip @ 1500 - 1900 psi. (100 – 130 bar) Alternatively, use a 517 tip @ 2300 – 2700 psi (158 - 186 bar).

*Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.*

### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** Dependent on temperature and humidity.

**Recoat:** 2-4 hours.

### Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty, please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly or consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/sustainability](https://duluxtrade.co.uk/sustainability).



Issued 03/25

1032

## ADVANCED CONTRACT MATT

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

**Ready Mixed:** This product contains max. 0.6g/l VOC.

VOC content: Trace (<0.1%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on 0333 222 70 70.

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2025.